

DXN
1

ATEX Plugs and Sockets 20A



Code :	II 2 GD EEx de IIC T5/T6 IP66/67
Certificate :	LCIE 99 ATEX 6027X
Zone :	Zone 1-2-21-22
Degree of protection :	IP66/67
Material :	Polyamide
Current:	20A
Max. Voltage:	550V
IK:	IK08
Temperature:	-40°C to +60°C

Socket	Plug	Voltage 50Hz	Phases
251408A	251808A	20-24V	2P
2514032	2518032	190-230V	2P+T
2514033	2518033	190-230V	3P+T
2514015	2518015	220-250V	1P+N+T
2514013	2518013	380-440V	3P+T
2514017	2518017	380-440V	3P+N+T
2514093	2518093	480-500V	3P+T
2514097	2518097	480-500V	3P+N+T

Each socket needs to be installed with a Wall box, handle or elbow



Part number	Description	Cable entry
251AB5316P	Wall box 30°	5-10mm
251AB53	Wall box 30°	M20, 10-14mm
251AB5325P	Wall box 30°	M25, 12-18mm
251AB8820P	Wall box 30°	M20, 10-14mm
251AB8825P	Wall box 30°	M25, 12-18mm
251AB8832P	Wall box 30°	M32, 16-25mm
251A057	Elbow 30°	-
251A757	Elbow 70°	-
251A753	Handle	M20, 10-14mm
251A75325P	Handle	M25, 12-18mm
251A75332P	Handle	M32, 16-25mm